

# T6-USB

USB Controlled With Computer

P/N:T6-USB



## Features

- . SP6T RF Electromechanical Switches With Internal Terminations
- . Small Size 108x50.8x50.8mm
- . Broadband RF Frequency Range:DC-18GHZ
- . USB Remote Controlled
- . Operating in Windows 32/64 Bit System
- . Configurable into SPST,SP2T,SP3T,SP4T,SP5T,SP6T etc.
- . Local LED Indicator For RF Patch

## Applications:

- . ATE System
- . EMC testing
- . Lab and RF Control equipment
- . Test for WLAN,WIFI,LTE and Wireless System

## RF SPEC.

Frequency Range	DC-3GHZ	3-6GHZ	6-12.4GHZ	12.4-18GHZ
VSWR	<1.20	<1.30	<1.40	<1.50
Insertion Loss	<0.2dB	<0.3dB	<0.40dB	<0.50dB
Isolation	>80dB	>70dB	>65dB	>60dB
*Power Handing(CW)	85W	40W	20W	10W
Terminations Power Handing(CW)	1W			



Tel :0086-10-82087227

Fax:0086-10-82087380

E-mail: [rfswitch@126.com](mailto:rfswitch@126.com)

Web site: [www.rf-switch.com](http://www.rf-switch.com)

- . RF Impedance: 50 ohm
- . RF Interface:SMA female
- . Switching Time: <40ms
- . Life:>200, 0000 cycles
- . Switching Sequence:Break Before Make
- . Operating Temperature: -20 ~ +50℃
- . Power Supply:DC12V/4W

### Accessories:

- . **T6-USB Case**
- . **USB Cable Length=1.5m**
- . **AC/DC12V Power Adaptor**
- . **Remot Controlled Software**

### SIZE

